

Geoelectric Observation used by the Telegraphic Facilities of NTT Corporation

CONTENTS

1. Introduction
2. Observation method
3. Outline of the observed records
 - 3-1 Outline of the records at each observation group
 - 3-2 Comparison of the observed record in the same time of a different day
4. Long-term stability
5. Impedance tensor and transfer function
 - 5-1 Impedance tensor at the Shimodate group and at Kakioka
 - 5-2 Impedance tensor at the Mito group and transfer function at Kakioka
6. Time changes of impedance tensors and transfer functions
7. Elimination of the electrical fields induced by geomagnetic variations - Detection of the anomalous earth potential -
 - 7-1 Analysis method by a stochastic differential equation
 - 7-2 For geoelectric fields between Kasama and Mito
 - 7-3 Application to the data of electrical fields at the Mito group and Z at Kakioka
 - 7-4 Spectral analysis
 - 7-5 When using per-minute data
 - 7-6 Use of the transfer function and impedance tensor
8. Relation to tectonic activities
 - 8-1 Relation to the earthquake swarms off the east coast of the Izu Peninsula
 - 8-2 Relation to eruptions of Izu-Oshima volcano
 - 8-3 Other changes
9. Relation to tide, atmospheric pressure and others
10. Application for research of fault structure
 - 10-1 Iriyama fault
 - 10-2 Tanna fault
 - 10-3 Fujikawa fault
11. Anomalous geoelectric change observed near CA (conductivity anomaly) boundary
12. Electrical observation on the sea floor by making use of the power-feeding arrangement of the Permanent Ocean-Bottom Seismograph Observation System off Boso Peninsula (BSOBS)
13. Conclusions
14. Circumstances of observation and acknowledgements

References